

AB2500 HD



▲ Function

- Enable slotting, creasing, scoring, slitting, trimming, glue flap crash, and hole punching in one pass
- Capable of processing corrugated cardboard from E to AAA flute.
- Slot width ranges from 7mm to 14mm
- Patent-designed slotting structure allows for slotting lengths from 5mm to 1000mm without changing slotting knives.
- Patented double-sided creasing design, making folds much easier and more aesthetically pleasing.
- Patented misaligned creasing design allows for continuous production without interruptions, resulting in faster production speeds.

▲ Specification

Equipment Size	3700(W)*2600(H)*3400(L)mm
Weight	Approx. 7000kg
Power	380V, 20KW
Production Rate	Approx. 500 pcs/Hour
Sheet Type	Corrugated Sheet
Switchover Time	5-15 Seconds
Cardboard Thickness	1.5-16mm
Max. Board Size	2500(W)mm*Unlimited(L)
Min. Board Size	430(W)*700(L)mm
Maximum Carton size	1000(W)*2400(H)mm*Unlimited(L)
Minimum Carton size	200(W)*170(H)*240(L)mm
Box Styles	Over 100 types

▲ Function

Pre-defined Box Types	✓	Glue Flap Crash	✓
Automatic Feeding	✓	Size Measurement	Optional
Slotting Scoring	✓	Gluing	Optional
Trimming	✓	Automatic Pallet Feeding	Optional
Slitting Creasing	✓	Automatic Stacking	Optional
Hole Puncher	✓	Printing	Optional